

# FEATURE WALL PRODUCT DATASHEET:



## PANEL SIZES AND WEIGHTS

---

2400 x 600 x 21mm = 14.75kg

3000 x 600 x 21mm = 18.5kg

Note each slat measures 27mm, with a 13mm recess in between.

## MATERIAL

---

- 12mm battens on an acoustic suppressing 9mm PET felt backing.
- Slat is made from black FSC® certified fire resistant MDF with a 0.6mm real wood veneer.
- Black felt backing is 9mm porous, polyester needle-felt, density 1300g/m<sup>2</sup>.

## FIRE RATING/ PERFORMANCE

---

Panels are Class B, s2, d0 fire rated.

## SOUND ABSORPTION

---

Class D

## STORAGE

---

All panels must be stored flat in a dry area until final fixing is undertaken.

## WARRANTY

---

1 year warranty against manufacturing defects from date of purchase.

## DISCLAIMER

---

Please ensure the panels are NOT installed in a damp environment. Due to the use of natural veneers, the product, if left exposed for long periods of time may be subject to slight fading which is a process where any natural fibres are exposed to UV rays. We reserve the right to alter and amend product and technical details without prior notice.

## CARE & MAINTENANCE

---

To maintain Feature Wall panels occasionally wipe down the slats with a damp lint free cloth. In addition, the use of a brush attachment on a vacuum cleaner is ideal to clean the recesses in between the slats.

Once installed we recommend the use of a wood treatment product on the wood veneer slats, such as Bona Oil Refresher, to help protect and create an even finish. Note that this process will need to be repeated as required. Please ensure you trial a good quality product on an offcut before applying to your Feature Wall panels.

For further information, contact; [info@feature-wall.co.uk](mailto:info@feature-wall.co.uk)